



## INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

### Certificate

TS ISO 8528

CE

SZUTEST

2000/14/EC

### General Characteristics

<b>Model Name</b>	APD 13 A
<b>Frequency (Hz)</b>	50
<b>Fuel Type</b>	Diesel
<b>Engine Made and Model</b>	AKSA - A4CRX19
<b>Alternator Made and Model</b>	Aksa - AK 109
<b>Control Panel Model</b>	DSE 6120
<b>Canopy</b>	ACP 1A

**3 Phase, 50 Hz, PF 0.8**

<b>VOLTAGE</b>	<b>STANDBY RATING (ESP)</b>	<b>PRIME RATING (PRP)</b>	<b>Standby Amper</b>
----------------	-----------------------------	---------------------------	----------------------



kVA	kW	kVA	kW		
400/231	12	9.60	11	8.80	17.32

**STANDBY RATING (ESP):** Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

**PRIME RATING (PRP):** Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.


### ENGINE SPECIFICATIONS

<b>Engine</b>		AKSA
<b>Engine Model</b>		A4CRX19
<b>NO. OF CYLINDERS AND BUILD</b>		4 cylinders - in line
<b>BORE AND STROKE</b>	<b>mm</b>	80 X 90
<b>TOTAL DISPLACEMENT</b>	<b>L</b>	1,809
<b>Aspiration</b>		Naturally Aspirated
<b>COMPRESSION RATIO</b>		18:1
<b>RATED SPEED (RPM)</b>	<b>d/dk</b>	1500
<b>OIL CAPACITY</b>	<b>L</b>	6
<b>Standby Power (kW/HP)</b>		13.7/18.4
<b>Prime Power</b>		12.5/16.7



<b>Block Heater QTY</b>		1
<b>Block Heater Power (Watt)</b>		500
<b>Fuel Type</b>		Diesel
<b>Injection Type and System</b>		Direct
<b>Type of Fuel Pump</b>		Direct
<b>Governor System</b>		Mechanic
<b>Operating Voltage (Vdc)</b>		12 Vdc
<b>Battery and Capacity (Qty/Ah)</b>		1x36
<b>Cooling Method</b>		Water Cooled
<b>Cooling Fan Air Flow (m3/min)</b>		112.64
<b>Coolant Capacity (engine only / with radiator) (lt)</b>		5/16.3
<b>Air Filter</b>		Dry Type
<b>Fuel Cons. Prime With %100 Load (lt/hr)</b>		

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



	4.19
<b>Fuel Cons. Prime With %75 Load (lt/hr)</b>	3.51
<b>Fuel Cons. Prime With %50 Load (lt/hr)</b>	2.42

**ALTERNATOR SPECIFICATIONS**


<b>Manufacturer</b>	Aksa
<b>Alternator Made and Model</b>	AK 109
<b>Frequency (Hz)</b>	Hz 50
<b>Power (kVA)</b>	kVA 11,3
<b>DESIGN</b>	Brushless
<b>VOLTAGE</b>	V 400
<b>Phase</b>	3
<b>A.V.R.</b>	SX460
<b>Voltage Regulation</b>	(+/-) 1,5%
<b>Insulation System</b>	H

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>Protection</b>		IP22
<b>Rated Power Factor</b>		0.8
<b>WEIGHT COMP. GENERATOR (Kg)</b>		95
<b>COOLING AIR (m<sup>3</sup>/min)</b>	<b>m<sup>3</sup></b>	4,26

### SIZE and WEIGHT

<b>Open Type</b>	<b>DRY WEIGHT (kg.) (kg.)</b>	<b>LENGTH (mm.)</b>	<b>WIDTH (mm.)</b>	<b>HEIGHT (mm.)</b>	<b>TANK CAPACITY (lt.) (Lt.)</b>
	760	1400	760	912	
<b>CANOPY</b>	<b>DRY WEIGHT (kg.) (kg.)</b>	<b>LENGTH (mm.)</b>	<b>WIDTH (mm.)</b>	<b>HEIGHT (mm.)</b>	<b>TANK CAPACITY (lt.) (Lt.)</b>
ACP 1A	515	1672	823	873	32

### STANDARD SPECIFICATIONS

- Protective grille for rotating and hot parts;
- Radiator with mechanical fan;
- Water cooled, Diesel engine
- Electric starter and charge alternator;
- Starting battery (with lead acid) including rack and cables;

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



- Engine coolant heater;
- Base frame design incorporates an integral fuel tank and anti-vibration isolators;
- Flexible fuel connection hoses;
- Single bearing, class H alternator;
- Industrial exhaust silencer and steel bellows supplied separately (for open sets);
- Static battery charger
- Manual for application and installation

### **OPTIONAL EQUIPMENTS**

#### **ENGINE**

- Remote Radiator Cooling
- Fuel-Water Separator Filter

#### **ALTERNATOR**

- Anti-Condensation Heater

#### **CONTROL SYSTEM**

- Charge Ammeter

#### **TRANSFER SWITCH**

- Three Pole Contactor
- Four Pole Contactor
- Three or four pole motor operated circuit breaker

#### **OTHER ACCESSORIES**

- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Residential silencer
- Enclosure: weather protective or sound attenuated
- Trailer
- Tool kit for maintenance



## Devices

- DSE, model 6120 Auto Mains Failure control module.
- Battery charger input 198-264 volt, output 27,6 V 5 A (24 V) or 13,8 Volt 5A (12V)
- Emergency stop push button and fuses for control circuits.

## Construction and finish

- Components installed in sheet steel enclosure. Phosphate chemical, pre-coating of steel provides corrosion resistant surface. Polyester composite powder topcoat forms high gloss and extremely durable finish. Lockable and hinged panel door provides easy access to components.

## Installation

Control panel is mounted on baseframe with steel stand. Located at the right side of the generator set (When you look at the Gen.Set. from Alternator)

## GENERATING SET CONTROL UNIT

The DSE 6120 module has been designed to monitor generator frequency, volt, current, engine oil pressure, coolant temperature running hours and battery volts.

Module monitors the mains supply and switch over to the generator when the mains power fails.

The DSE6120 also indicates operational status and fault conditions, Automatically shutting down the Gen. Set and giving true first up fault condition of Gen. Set failure. The LCD display indicates the fault.

### Стандартные функции

- Microprocessor controlled.
- LCD display makes information easy to read.
- Automatically transfers between mains (utility) and generator power.
- Manual programming on front panel.
- User-friendly set-up and button layout.
- Remote start.
- Event logging (50) showing date and time.
- Controls: Stop/Reset, Manual, Auto, Test, Start, buttons. An additional push button next to the LCD display is used to scroll through the modules' metering displays.

### Измерительные приборы

#### ENGINE

- Engine speed.

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



- Oil pressure.
- Coolant temperature.
- Run time.
- Battery volts.
- Configurable timing.

**GENERATOR**

- Voltage (L-L, L-N).
- Current (L1-L2-L3).
- Frequency.
- Gen. Set ready.
- Gen. Set enabled.

**MAINS**

- Mains ready.
- Mains enabled.

**Схема защиты****WARNING**

- Charge failure.
- Battery Low/High voltage.
- Fail to stop.
- Low /High generator voltage.
- Under /Over generator frequency.
- Over /Under speed.
- Low oil pressure.
- High coolant temperature.

**SHUT DOWNS**

- Fail to start.
- Emergency stop.
- Low oil pressure.
- High coolant temperature.
- Over /Under speed.
- Under/over generator frequency.
- Under/over generator voltage.
- Oil pressure sensor open.
- Coolant temperature sensor open.

**ELECTRICAL TRIP**

- Generator over current.

**Опционные особенности**

- Flexible sensor can be controlled with temperature, pressure, percentage (warning/shutdown/electrical

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.





trip)

- Local setting parameters and monitoring from PC to control module with USB connection (max 6 mt).

#### **Стандарты**

- Electrical Safety / EMC compatibility
- BS EN 60950 Electrical business equipment.
- BS EN 61000-6-2 EMC immunity standard.
- BS EN 61000-6-4 EMC emission standard.

### **STATIC BATTERY CHARGER**

- Battery charger is manufactured with switching-mode and SMD technology and it has high efficiency.
- Battery charger models' output V-I characteristic is very close to square and output is 5 amper, 13,8 V for 12 volt and 27,6 V for 24 V . Input 198 - 264 volt AC.
- The charger is fitted with a protection diode across the output.
- Connect charge fail relay coil between positive output and CF output.
- They are equipped with RFI filter to reduce electrical noise radiated from the device.
- Galvanically isolated input and output typically 4kV for high reliability.

#### **Introduction**

Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies (8 – 275kVA) fit directly to the open generator set to provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

### **STANDARD SPECIFICATIONS**

Compact footprint, low profile design.

Enclosure, generator set, exhaust system and base-tank are pre-assembled, pre-integrated and shipped as one package

Body made from steel components treated with polyester powder coating

Fire retardant foam insulation

Easy access to all service points

Exhaust system inside canopy

Large doors on each side

Control panel viewing window in a lockable access door

Emergency stop push button mounted on enclosure exterior

Cooling fan and battery charging alternator fully guarded

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Fuel fill and battery can only be reached via lockable access doors.  
Lifting points on the top of canopy and base frame  
Customer options available to meet your applications needs.

<b>CANOPY MODEL</b>		ACP 1
<b>WIDTH</b>	<b>mm.</b>	823
<b>LENGTH</b>	<b>mm.</b>	1522
<b>HEIGHT</b>	<b>mm.</b>	1127
<b>TANK CAPACITY (lt.)</b>	<b>Lt.</b>	32

**STANDARD SPECIFICATIONS**

Compact footprint, low profile design.  
Enclosure, generator set, exhaust system and base-tank are pre-assembled, pre-integrated and shipped as one package  
Body made from steel components treated with polyester powder coating  
Fire retardant foam insulation  
Easy access to all service points  
Exhaust system inside canopy  
Large doors on each side  
Control panel viewing window in a lockable access door  
Emergency stop push button mounted on enclosure exterior  
Cooling fan and battery charging alternator fully guarded  
Fuel fill and battery can only be reached via lockable access doors.  
Lifting points on the top of canopy and base frame  
Customer options available to meet your applications needs.

<b>CANOPY MODEL</b>		ACP 1A
<b>WIDTH</b>	<b>mm.</b>	823

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>LENGTH</b>	<b>mm.</b>	1672
<b>HEIGHT</b>	<b>mm.</b>	873
<b>TANK CAPACITY (lt.)</b>	<b>Lt.</b>	32

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.