



## INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby applications. All generator sets are factory build, and production tested.

### General Characteristics

<b>Model Name</b>	APD 220 C
<b>Frequency (Hz)</b>	50
<b>Fuel Type</b>	Diesel
<b>Engine Made and Model</b>	CUMMINS - 6CTAA8.3-G2
<b>Alternator Made and Model</b>	Aksa - AK 4160
<b>Control Panel Model</b>	DSE 7320
<b>Canopy</b>	MS 60 CK

### 3 Количество фаз, 50 Hz, PF 0.8

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	



400/231	220	176.00	200	160.00	317.55
---------	-----	--------	-----	--------	--------

**STANDBY RATING (ESP)** : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

**PRIME RATING (PRP)** : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

### ENGINE SPECIFICATIONS

<b>Engine</b>		CUMMINS
<b>Engine Model</b>		6CTAA8.3-G2
<b>NO. OF CYLINDERS AND BUILD</b>		6 cylinders - in line
<b>BORE AND STROKE</b>	<b>mm</b>	114 X 135
<b>TOTAL DISPLACEMENT</b>	<b>L</b>	8,30
<b>Aspiration</b>		Turbo Charged and Charge Air Cooled
<b>COMPRESSION RATIO</b>		18:1
<b>RATED SPEED (RPM)</b>	<b>d/dk</b>	1500
<b>OIL CAPACITY</b>	<b>L</b>	23,8

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>Standby Power (kW/HP)</b>	203/272	
<b>Prime Power</b>	183/245	
<b>Block Heater QTY</b>		
		1
<b>Block Heater Power (Watt)</b>		
		1500
<b>Fuel Type</b>		
		Diesel
<b>Injection Type and System</b>		
		Direct
<b>Type of Fuel Pump</b>		
		BYC P7100
<b>Governor System</b>		
		Electronic
<b>Operating Voltage (Vdc)</b>		
		24 Vdc



<b>Battery and Capacity (Qty/Ah)</b>			
		2x85	
<b>Charge Alternator (A)</b>			
		40	
<b>Cooling Method</b>			
		Water Cooled	
<b>Cooling Fan Air Flow (m3/min)</b>			
		325,8	
<b>Coolant Capacity (engine only / with radiator) (lt)</b>			
		12.3/47.3	
<b>Air Filter</b>			
		Dry Type	
<b>Fuel Cons. Prime With %100 Load (lt/hr)</b>			
		45	
<b>Fuel Cons. Prime With %75 Load (lt/hr)</b>			
		34	


**Fuel Cons. Prime With %50 Load (lt/hr)**

23

**ALTERNATOR SPECIFICATIONS**



<b>Manufacturer</b>		Aksa
<b>Alternator Made and Model</b>		AK 4160
<b>Frequency (Hz)</b>	<b>Hz</b>	50
<b>Power (kVA)</b>	<b>kVA</b>	200
<b>DESIGN</b>		Brushless
<b>VOLTAGE</b>	<b>V</b>	400
<b>Phase</b>		3
<b>A.V.R.</b>		SX440
<b>Voltage Regulation</b>	<b>(+/-)</b>	1
<b>Insulation System</b>		H
<b>Protection</b>		IP22

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>Rated Power Factor</b>	0.8
<b>WEIGHT COMP. GENERATOR (Kg)</b>	626
<b>COOLING AIR (m<sup>3</sup>/min)</b>	m <sup>3</sup> 30.84

### SIZE and WEIGHT

Open Type	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
	2300	2750	1300	1734	470
CANOPY	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
MS 60 CK 	2930	3963	1356	2171	470

### STANDART SPECIFICATIONS

Water cooled, Diesel engine  
 Radiator with mechanical fan  
 Protective grille for rotating and hot parts  
 Electric starter and charge alternator  
 Starting battery (with lead acid) including rack and cables  
 Engine coolant heater

Производителъ сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Base frame design incorporates an integral fuel tank and anti-vibration isolators  
Flexible fuel connection hoses  
Single bearing, class H alternator  
Industrial exhaust silencer and steel bellows supplied separately (for open sets)  
Static battery charger  
Manual for application and installation

### **OPTIONAL EQUIPMENTS**

#### **ENGINE**

- Fuel-Water Separator Filter
- Low water level alarm
- Oil heater

#### **ALTERNATOR**

- Anti-Condensation Heater
- Main line circuit breaker

#### **CONTROL SYSTEM**

- Earth fault, single set
- Charge Ammeter

#### **TRANSFER SWITCH**

- Three Pole Contactor
- Four Pole Contactor



- Three or four pole motor operated circuit breaker

#### **OTHER ACCESSORIES**

- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Low and high fuel level alarm
- Enclosure: weater protective or sound attenuated
- Trailer
- Tool kit for maintenance

#### **INTRODUCTION**

Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

#### **STANDARD SPECIFICATIONS**

Compact footprint, low profile design.

Enclosure, generator set, exhaust system and fuel tank are pre-ssembled, pre-integrated and shipped as one package

Body made from steel components treated with polyester powder coating

Fire retardant foam insulation

Easy access to all service points

Exhaust system inside canopy

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.





Large doors on each side

Control panel viewing window in a lockable access door

Emergency stop push button mounted on enclosure exterior

Cooling fan and battery charging alternator fully guarded

Fuel fill and battery can only be reached via lockable access doors.

Lifting points on the top of canopy and base frame

Customer options available to meet your applications needs.

Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of the noise level test has been approved by the notified body Szutest

<b>CANOPY MODEL</b>		MS 60 CK
<b>WIDTH</b>	<b>mm.</b>	1356
<b>LENGTH</b>	<b>mm.</b>	3963
<b>HEIGHT</b>	<b>mm.</b>	2171
<b>TANK CAPACITY (lt.)</b>	<b>Lt.</b>	470