



INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Certificate

TS ISO 8528

TS ISO 9001-2008

CE

SZUTEST

2000/14/EC

General Characteristics

| | |
|----------------------------------|--------------------------------|
| Model Name | AJD 220 |
| Frequency (Hz) | 50 |
| Fuel Type | Diesel |
| Engine Made and Model | JOHN DEERE - 6068HFG20 (202kW) |
| Alternator Made and Model | Mecc Alte - ECO 38-2S/4 A |
| Control Panel Model | DSE 7320 |
| Canopy | AK 49 |

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.


3 Phase, 50 Hz, PF 0.8

| VOLTAGE | STANDBY RATING (ESP) | | PRIME RATING (PRP) | | Standby Amper |
|---------|----------------------|--------|--------------------|--------|---------------|
| | kVA | kW | kVA | kW | |
| 400/231 | 220 | 176.00 | 200 | 160.00 | 317.55 |

STANDBY RATING (ESP) : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

PRIME RATING (PRP) : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

ENGINE SPECIFICATIONS

| | | |
|-----------------------------------|-----------|--|
| Engine | | JOHN DEERE |
| Engine Model | | 6068HFG20 (202kW) |
| NO. OF CYLINDERS AND BUILD | | 6 cylinders - in line |
| BORE AND STROKE | mm | 106 X 127 |
| TOTAL DISPLACEMENT | L | 6,8 |
| Aspiration | | Turbo Charged and Air to Air AfterCooled |

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



| | | | |
|----------------------------------|-------------|---------------------------|--|
| COMPRESSION RATIO | | 17.0:1 | |
| RATED SPEED (RPM) | d/dk | 1500 | |
| OIL CAPACITY | L | 32 | |
| Standby Power (kW/HP) | | 202/271 | |
| Prime Power | | 184/247 | |
| Block Heater QTY | | | |
| | | 1 | |
| Block Heater Power (Watt) | | | |
| | | 1500 | |
| Fuel Type | | | |
| | | Diesel | |
| Injection Type and System | | | |
| | | Direct | |
| Type of Fuel Pump | | | |
| | | Stanadyne DB4 Rotary Type | |



| | | | |
|--|--|--------------|--|
| Governor System | | | |
| | | Mechanic | |
| Operating Voltage (Vdc) | | | |
| | | 12 Vdc | |
| Battery and Capacity (Qty/Ah) | | | |
| | | 1x85 | |
| Cooling Method | | | |
| | | Water Cooled | |
| Coolant Capacity (engine only / with radiator) (lt) | | | |
| | | 11.3/27.3 | |
| Air Filter | | | |
| | | Dry Type | |
| Fuel Cons. Prime With %100 Load (lt/hr) | | | |
| | | 44.55 | |
| Fuel Cons. Prime With %75 Load (lt/hr) | | | |
| | | 35.06 | |



| | | | |
|---|--|--|-------|
| Fuel Cons. Prime With %50 Load (lt/hr) | | | |
| | | | 22.98 |



ALTERNATOR SPECIFICATIONS

| | | |
|----------------------------------|--------------|---------------|
| Manufacturer | | Mecc Alte |
| Alternator Made and Model | | ECO 38-2S/4 A |
| Frequency (Hz) | Hz | 50 |
| Power (kVA) | kVA | 200 |
| DESIGN | | Brushless |
| VOLTAGE | V | 400 |
| Phase | | 3 |
| A.V.R. | | DSR |
| Voltage Regulation | (+/-) | 1 |
| Insulation System | | H |
| Protection | | IP23 |



| | |
|--|-------------------|
| Rated Power Factor | 0.8 |
| WEIGHT COMP. GENERATOR (Kg) | 560 |
| COOLING AIR (m³/min) | m ³ 32 |

SIZE and WEIGHT

| Open Type | DRY WEIGHT (kg.) (kg.) | LENGTH (mm.) | WIDTH (mm.) | HEIGHT (mm.) | TANK CAPACITY (lt.) (Lt.) |
|--|---------------------------|-----------------|----------------|-----------------|---------------------------|
|  | | 2300 | 1080 | 1838 | 340 |
| CANOPY | DRY WEIGHT (kg.) (kg.) | LENGTH (mm.) | WIDTH (mm.) | HEIGHT (mm.) | TANK CAPACITY (lt.) (Lt.) |
| AK 49  | | 3404 | 1136 | 2020 | 340 |

STANDART SPECIFICATIONS

- Water cooled, Diesel engine
- Radiator with mechanical fan
- Protective grille for rotating and hot parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine coolant heater
- Base frame design incorporates an integral fuel tank and anti-vibration isolators

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Flexible fuel connection hoses
Single bearing, class H alternator
Industrial exhaust silencer and steel bellows supplied separately (for open sets)
Static battery charger
Manual for application and installation

OPTIONAL EQUIPMENTS

ENGINE

- Electronic governor control
- Fuel-Water Separator Filter
- Low water level alarm
- Oil heater

ALTERNATOR

- Anti-Condensation Heater
- Over sized alternator
- Main line circuit breaker

CONTROL SYSTEM

- Remote annunciator panel
- Earth fault, single set
- Charge Ammeter

TRANSFER SWITCH

- Three or four pole contactor
- Three or four pole motor operated circuit breaker

OTHER ACCESSORIES

- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Electrical oil drain pump
- Low and high fuel level alarm
- Residential silencer
- Enclosure: weater protective or sound attenuated
- Duct adapter (on radiator)
- Inlet and outlet motorised louvers
- Inlet and outlet acoustic baffles
- Trailer
- Tool kit for maintenance
- 1500/3000 hours maintenance kit



- Double wall chassis
- Supplied with oil and coolant - 30 °C
- Battery isolating switch

INTRODUCTION

Sound-attenuated and Weather-protective Enclosures Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

STANDARD SPECIFICATIONS

Compact footprint, low profile design.

Enclosure, generator set, exhaust system and fuel tank are pre-ssembled, pre-integrated and shipped as one package

Body made from steel components treated with polyester powder coating

Fire retardant foam insulation

Easy access to all service points

Exhaust system inside canopy

Large doors on each side

Control panel viewing window in a lockable access door

Emergency stop push button mounted on enclosure exterior

Cooling fan and battery charging alternator fully guarded

Fuel fill and battery can only be reached via lockable access doors.

Lifting points on the top of canopy and base frame

Customer options available to meet your applications needs.

Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of the noise level test has been approved by the notified body Szutest

| | | |
|---------------------|------------|-------|
| CANOPY MODEL | | AK 49 |
| WIDTH | mm. | 1147 |
| LENGTH | mm. | 3402 |

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



| | | |
|----------------------------|------------|------|
| HEIGHT | mm. | 2007 |
| TANK CAPACITY (lt.) | Lt. | 340 |