



## INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

### Certificate

TS ISO 8528

TS ISO 9001-2008

CE

SZUTEST

2000/14/EC

### General Characteristics

<b>Model Name</b>	APD 220 A
<b>Frequency (Hz)</b>	50
<b>Fuel Type</b>	Diesel
<b>Engine Made and Model</b>	AKSA - A6CRX97TI
<b>Alternator Made and Model</b>	Aksa - AK 4160
<b>Control Panel Model</b>	DSE 6020
<b>Canopy</b>	ASM 7

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.


**3 Phase, 50 Hz, PF 0.8**

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
400/231	220	176.00	200	160.00	317.55

**STANDBY RATING (ESP)** : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

**PRIME RATING (PRP)** : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

### ENGINE SPECIFICATIONS

<b>Engine</b>		AKSA
<b>Engine Model</b>		A6CRX97TI
<b>NO. OF CYLINDERS AND BUILD</b>		6 cylinders - in line
<b>BORE AND STROKE</b>	<b>mm</b>	126 X 130
<b>TOTAL DISPLACEMENT</b>	<b>L</b>	9,73
<b>Aspiration</b>		Turbo Charged and Intercooled(Water to Air)

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>COMPRESSION RATIO</b>		16.5:1	
<b>RATED SPEED (RPM)</b>	<b>d/dk</b>	1500	
<b>OIL CAPACITY</b>	<b>L</b>	16	
<b>Standby Power (kW/HP)</b>		252/338	
<b>Block Heater QTY</b>			
		1	
<b>Block Heater Power (Watt)</b>			
		1500	
<b>Fuel Type</b>			
		Diesel	
<b>Injection Type and System</b>			
		Direct	
<b>Type of Fuel Pump</b>			
		P pump	
<b>Governor System</b>			
		Electronic	

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>Operating Voltage (Vdc)</b>			
		24 Vdc	
<b>Battery and Capacity (Qty/Ah)</b>			
		2x120	
<b>Cooling Method</b>			
		Water Cooled	
<b>Cooling Fan Air Flow (m3/min)</b>			
		450	
<b>Coolant Capacity (engine only / with radiator) (lt)</b>			
		/65	
<b>Air Filter</b>			
		Dry Type	
<b>Fuel Cons. Prime With %100 Load (lt/hr)</b>			
		54.1	
<b>Fuel Cons. Prime With %75 Load (lt/hr)</b>			
		40.6	



<b>Fuel Cons. Prime With %50 Load (lt/hr)</b>		
		27.1


**ALTERNATOR SPECIFICATIONS**

<b>Manufacturer</b>		Aksa
<b>Alternator Made and Model</b>		AK 4160
<b>Frequency (Hz)</b>	<b>Hz</b>	50
<b>Power (kVA)</b>	<b>kVA</b>	200
<b>DESIGN</b>		Brushless
<b>VOLTAGE</b>	<b>V</b>	400
<b>Phase</b>		3
<b>A.V.R.</b>		SX440
<b>Voltage Regulation</b>	<b>(+/-)</b>	1
<b>Insulation System</b>		H
<b>Protection</b>		IP22



<b>Rated Power Factor</b>	0.8
<b>WEIGHT COMP. GENERATOR (Kg)</b>	626
<b>COOLING AIR (m<sup>3</sup>/min)</b>	m <sup>3</sup> 30.84

### SIZE and WEIGHT

Open Type	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
	-	-	-	-	
CANOPY	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
ASM 7	2980	3918	1463	2163	526

### STANDART SPECIFICATIONS

- Water cooled, Diesel engine
- Radiator with mechanical fan
- Protective grille for rotating and hot parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine coolant heater
- Base frame design incorporates an integral fuel tank and anti-vibration isolators
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel bellows supplied separately(for open sets)

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Static battery charger  
Manual for application and installation

## **OPTIONAL EQUIPMENTS**

### **ENGINE**

- Fuel-Water Separator Filter
- Oil heater

### **ALTERNATOR**

- Anti-Condensation Heater
- Main line circuit breaker

### **CONTROL SYSTEM**

- Charge Ammeter

### **TRANSFER SWITCH**

- Three Pole Contactor
- Four Pole Contactor
- Three or four pole motor operated circuit breaker

### **OTHER ACCESSORIES**

- Main Fuel Tank
- Automatic or manual fuel filling system

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



- Manual oil drain pump
- Low and high fuel level alarm
- Enclosure: weater protective or sound attenuated
- Trailer
- Tool kit for maintenance

## INTRODUCTION

Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies (8 – 275kVA) fit directly to the open generator set to provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

## STANDARD SPECIFICATIONS

Compact footprint, low profile design.

Enclosure, generator set, exhaust system and base-tank are pre-assembled, pre-integrated and shipped as one package

Body made from steel components treated with polyester powder coating

Fire retardant foam insulation

Easy access to all service points

Exhaust system inside canopy

Large doors on each side

Control panel viewing window in a lockable access door

Emergency stop push button mounted on enclosure exterior

Cooling fan and battery charging alternator fully guarded

Fuel fill and battery can only be reached via lockable access doors.

Lifting points on the top of canopy and base frame

Customer options available to meet your applications needs.





<b>CANOPY MODEL</b>		ASM 7
<b>WIDTH</b>	<b>mm.</b>	1463
<b>LENGTH</b>	<b>mm.</b>	3918
<b>HEIGHT</b>	<b>mm.</b>	2163
<b>TANK CAPACITY (lt.)</b>	<b>Lt.</b>	526

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.