



INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Certificate

TS ISO 8528

CE

SZUTEST

2000/14/EC

General Characteristics

Model Name	AP 715
Frequency (Hz)	50
Fuel Type	Diesel
Engine Made and Model	PERKINS - 2806A-E18TAG2
Alternator Made and Model	Mecc Alte - ECO 40-3L/4C
Control Panel Model	DSE 7320
Canopy	MS 86-AP660

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.


3 Phase, 50 Hz, PF 0.8

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
400/231	715	572.00	650	520.00	1032.04

STANDBY RATING (ESP) : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

PRIME RATING (PRP) : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

ENGINE SPECIFICATIONS

Engine		PERKINS
Engine Model		2806A-E18TAG2
NO. OF CYLINDERS AND BUILD		6 cylinders - in line
BORE AND STROKE	mm	145 X 183
TOTAL DISPLACEMENT	L	18,13
Aspiration		Turbo Charged and Charge Air Cooled

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



COMPRESSION RATIO		14,5:1	
RATED SPEED (RPM)	d/dk	1500	
OIL CAPACITY	L	62	
Standby Power (kW/HP)		628/841,82	
Prime Power		584/782,84	
Block Heater QTY			
		1	
Block Heater Power (Watt)			
		3000	
Fuel Type			
		Diesel	
Type of Fuel Pump			
		MEUI	
Governor System			
		ECM	



Operating Voltage (Vdc)			
		24 Vdc	
Battery and Capacity (Qty/Ah)			
		2x143	
Charge Alternator (A)			
		55	
Cooling Method			
		Water Cooled	
Cooling Fan Air Flow (m3/min)			
		702	
Coolant Capacity (engine only / with radiator) (lt)			
		/61	
Air Filter			
		Dry Type	
Fuel Cons. Prime With %100 Load (lt/hr)			
		132	



Fuel Cons. Prime With %75 Load (lt/hr)			
		97	
Fuel Cons. Prime With %50 Load (lt/hr)			
		66	



ALTERNATOR SPECIFICATIONS

Manufacturer		Mecc Alte
Alternator Made and Model		ECO 40-3L/4C
Frequency (Hz)	Hz	50
Power (kVA)	kVA	680
DESIGN		4 Pole, Brushless
VOLTAGE	V	400
Phase		3
A.V.R.		DER1
Voltage Regulation	(+/-)	0.5



Insulation System	H
Protection	IP23
Rated Power Factor	0.8
WEIGHT COMP. GENERATOR (Kg)	1534
COOLING AIR (m³/min)	m ³ 54

SIZE and WEIGHT

Open Type	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
	4850	3450	1800	2171	1150
CANOPY	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
MS 86-AP660 	5750	5383	1800	2503	1150



STANDART SPECIFICATIONS

Water cooled, Diesel engine
Radiator with mechanical fan
Protective grille for rotating and hot parts
Electric starter and charge alternator
Starting battery (with lead acid) including rack and cables
Engine coolant heater
Base frame design incorporates an integral fuel tank and anti-vibration isolators
Flexible fuel connection hoses
Single bearing, class H alternator
Industrial exhaust silencer and steel bellows supplied separately (for open sets)
Static battery charger
Manual for application and installation

OPTIONAL EQUIPMENTS

ENGINE

Fuel-Water Seperator Filter
Oil heater

ALTERNATOR

Anti-Condensation Heater
Over sized alternator
PMG excitation + AVR
Main line circuit breaker

CONTROL SYSTEM


Remote annunciator panel
Remote relay output
Alarm output relays
Remote communication with modem
Earth fault, single set
Charge Ammeter

TRANSFER SWITCH

Three or four pole contactor
Three or four pole motor operated circuit breaker

OTHER ACCESSORIES

Main Fuel Tank
Automatic or manual fuel filling system
Manual oil drain pump
Electrical oil drain pump
Residential silencer



Enclosure: weater protective or sound attenuated
Duct adapter (on radiator)
Inlet and outlet motorised louvers
Inlet and outlet acoustic baffles
Trailer Tool kit for maintenance
Supplied with oil and coolant - 30 °C
Battery isolating switch

INTRODUCTION

Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

STANDARD SPECIFICATIONS

Compact footprint, low profile design.
Enclosure, generator set, exhaust system and fuel tank are pre-ssembled, pre-integrated and shipped as one package
Body made from steel components treated with polyester powder coating
Fire retardant foam insulation
Easy access to all service points
Exhaust system inside canopy
Large doors on each side
Control panel viewing window in a lockable access door
Emergency stop push button mounted on enclosure exterior
Cooling fan and battery charging alternator fully guarded
Fuel fill and battery can only be reached via lockable access doors.
Lifting points on the top of canopy and base frame
Customer options available to meet your applications needs.
Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of the noise level test has been aproved by the notified body Szutest

CANOPY MODEL	MS 86-AP660
---------------------	-------------



WIDTH	mm.	1800
LENGTH	mm.	5383
HEIGHT	mm.	2503
TANK CAPACITY (lt.)	Lt.	1150

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.