INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Certificate

TS ISO 8528

CE

SZUTEST

2000/14/EC

General Characteristics

Model Name	APD 1400 BD
Frequency (Hz)	50
Fuel Type	Diesel
Engine Made and Model	BAUDOUIN - 12M33G1400/5
Alternator Made and Model	Aksa - AK71120
Control Panel Model	DSE 7320
Canopy	AK 96-AP1400

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

3 Phase, 50 Hz, PF 0.8

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
400/231	1400	1120.00	1270	1016.00	2020.79

STANDBY RATING (ESP) : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

PRIME RATING (PRP) : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour perod of operation.

ENGINE SPECIFICATIONS

Engine		BAUDOUIN
Engine Model		12M33G1400/5
NO. OF CYLINDERS AND BUILD		12 cylinders - V type
BORE AND STROKE	**mm**	150 X 185
TOTAL DISPLACEMENT	**L**	39,2
Aspiration		Turbo Charged and Air to Air AfterCooled

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

COMPRESSION RATIO		15:1
RATED SPEED (RPM)	**d/dk**	1500
OIL CAPACITY	**L**	160
Standby Power (kW/HP)		1210/1623
Prime Power		1100/1475
Block Heater QTY		2
Block Heater Power (Watt)		3000
Fuel Type		Diesel
Injection Type and System		Direct
Type of Fuel Pump		Mechanical

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

Governor System		Electronic
Operating Voltage (Vdc)		24 Vdc
Battery and Capacity (Qty/Ah)		2x143
Charge Alternator (A)		55
Cooling Method		Water Cooled
Cooling Fan Air Flow (m3/min)		1140
Coolant Capacity (engine only / with radiator) (lt)		105/159
Air Filter		Dry Type

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

Fuel Cons. Prime With %100 Load (lt/hr)			
		258.6	
Fuel Cons. Prime With %75 Load (lt/hr)			
		190.7	
Fuel Cons. Prime With %50 Load (lt/hr)			
		129.2	

ALTERNATOR SPECIFICATIONS

Manufacturer		Aksa
Alternator Made and Model		AK71120
Frequency (Hz)	**Hz**	50
Power (kVA)	**kVA**	1400
DESIGN		Brushless
VOLTAGE	**V**	400
Phase		3

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

A.V.R.		MX341
Voltage Regulation	**(+/-)**	1
Insulation System		H
Protection		IP22
Rated Power Factor		0.8
WEIGHT COMP. GENERATOR (Kg)		2760
COOLING AIR (m^3/min)	**m^3**	2.69

SIZE and WEIGHT

Open Type	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
Image not found or type unknown		4828	1868	2545	2000
CANOPY	**DRY WEIGHT (kg.) (kg.)**	**LENGTH (mm.)**	**WIDTH (mm.)**	**HEIGHT (mm.)**	**TANK CAPACITY (lt.) (Lt.)**

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

AK 96-AP1400 Image not found or type unknown		7500	2300	2495	1900

STANDART SPECIFICATIONS

Water cooled diesel engine
Radiator with mechanical fan
Protective grille for rotating and hot parts
Electric starter and charge alternator
Starting battery (with lead acid) including rack and cables
Engine coolant heater
Steel base frame and anti-vibration isolators
Spare external fuel tank (open set)
Flexible fuel connection hoses
Single bearing, class H alternator
Critical type exhaust silencer and steel bellows supplied separately
Static battery charger
Manual for application and installation
Generators Sets' voltage and frequency regulation comply with ISO 8528-5

OPTIONAL EQUIPMENTS

ENGINE
• Fuel-Water Seperator Filter
• Oil heater

ALTERNATOR
• Anti-Condensation Heater
• Over sized alternator
• PMG excitation + AVR
• Main line circuit breaker

CONTROL SYSTEM
• Automatic synchronising and power control system (multi gen-set Parallel)
• Transition synchronization with mains
• Remote annunciator panel
• Remote relay output

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

- Alarm output relays
- Remote communication with modem
- Earth fault, single set
- Charge Ammeter

TRANSFER SWITCH
- Three Pole Contactor
- Four Pole Contactor
- Three or four pole motor operated circuit breaker

OTHER ACCESSORIES
- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Electrical oil drain pump
- Low and high fuel level alarm
- Residential silencer
- Enclosure: weater protective or sound attenuated
- Duct adapter (on radiator)
- Inlet and outlet motorised louvers
- Inlet and outlet acoustic baffles
- Trailer
- Tool kit for maintenance
- Automatic transfer switch

INTRODUCTION

Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

STANDARD SPECIFICATIONS

Compact footprint, low profile design.
Enclosure, generator set, exhaust system and fuel tank are pre-ssembled, pre-integrated and shipped as one package
Body made from steel components treated with polyester powder coating

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

Fire retardant foam insulation
Easy access to all service points
Exhaust system inside canopy
Large doors on each side
Control panel viewing window in a lockable access door
Emergency stop push button mounted on enclosure exterior
Cooling fan and battery charging alternator fully guarded
Fuel fill and battery can only be reached via lockable access doors.
Lifting points on the top of canopy and base frame
Customer options available to meet your applications needs.
Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of the noise level test has been aproved by the notified body Szutest

CANOPY MODEL		AK 96-AP1400
WIDTH	**mm.**	2300
LENGTH	**mm.**	7500
HEIGHT	**mm.**	2495
TANK CAPACITY (lt.)	**Lt.**	1900

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.