



## INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

**\*The indicated PRP Power is for reference only. This engine is designed for emergency standby power (ESP) applications only.**

### Certificate

TS ISO 8528

CE

SZUTEST

2000/14/EC

### General Characteristics

<b>Model Name</b>	APD 2500 BD
<b>Frequency (Hz)</b>	50
<b>Fuel Type</b>	Diesel
<b>Engine Made and Model</b>	BAUDOUIN - 20M33G2500/5
<b>Alternator Made and Model</b>	Aksa - AK 72000
<b>Control Panel Model</b>	DSE 7320


**Canopy**

AK 100

**3 Phase, 50 Hz, PF 0.8**

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
400/231	2500	2000.00	2250	1800.00	3608.55

**STANDBY RATING (ESP)** : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

**PRIME RATING (PRP)** : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

### ENGINE SPECIFICATIONS

<b>Engine</b>		BAUDOUIIN
<b>Engine Model</b>		20M33G2500/5
<b>NO. OF CYLINDERS AND BUILD</b>		20 cylinders - V type
<b>BORE AND STROKE</b>	<b>mm</b>	150 X 185
<b>TOTAL DISPLACEMENT</b>	<b>L</b>	65.4

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>Aspiration</b>		Turbo Charged and Aftercooled(Air to Water)	
<b>COMPRESSION RATIO</b>		15:1	
<b>RATED SPEED (RPM)</b>	<b>d/dk</b>	1500	
<b>OIL CAPACITY</b>	<b>L</b>	235	
<b>Standby Power (kW/HP)</b>		2210/2964	
<b>Block Heater QTY</b>			
		2	
<b>Block Heater Power (Watt)</b>			
		3000	
<b>Fuel Type</b>			
		Diesel	
<b>Injection Type and System</b>			
		Direct	
<b>Type of Fuel Pump</b>			
		HPCR (High Pressure Common Rail)	



<b>Governor System</b>			
		ECU	
<b>Operating Voltage (Vdc)</b>			
		24 Vdc	
<b>Battery and Capacity (Qty/Ah)</b>			
		4x200	
<b>Charge Alternator (A)</b>			
		55	
<b>Cooling Method</b>			
		Water Cooled	
<b>Cooling Fan Air Flow (m3/min)</b>			
		2040	
<b>Coolant Capacity (engine only / with radiator) (lt)</b>			
		140/	
<b>Air Filter</b>			
		Dry Type	



Fuel Cons. Prime With %100 Load (lt/hr)			
		466.4	
Fuel Cons. Prime With %75 Load (lt/hr)			
		360.7	
Fuel Cons. Prime With %50 Load (lt/hr)			
		240.5	

**ТИП АЛЬТЕРНАТОРА**


Производитель		Aksa
генератор переменного тока марки и модели		AK 72000
Частота (Гц)	Hz	50
Мощность (кВА)	kVA	2500
дизайн		Brushless
Напряжение (В)	V	400
фаза		3

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>Регулятор напряжения</b>		MX341
<b>Система возбуждения</b>	<b>(+/-)</b>	1
<b>Класс изоляции</b>		H
<b>класс защиты</b>		IP22
<b>Активная мощность</b>		0.8
<b>Полный вес генератора (кг.)</b>		4760
<b>охлаждающий воздух</b>	<b>m<sup>3</sup></b>	161.4

**SIZE and WEIGHT**

<b>Open Type</b>	<b>DRY WEIGHT (kg.) (kg.)</b>	<b>LENGTH (mm.)</b>	<b>WIDTH (mm.)</b>	<b>HEIGHT (mm.)</b>	<b>TANK CAPACITY (lt.) (Lt.)</b>
 Image not found of type unknown		6760	2240	2842	
<b>CANOPY</b>	<b>DRY WEIGHT (kg.) (kg.)</b>	<b>LENGTH (mm.)</b>	<b>WIDTH (mm.)</b>	<b>HEIGHT (mm.)</b>	<b>TANK CAPACITY (lt.) (Lt.)</b>



AK 100 Image not found of type unknown		9633	2800	3307	2200
---	--	------	------	------	------

## STANDART SPECIFICATIONS

- Water cooled diesel engine
- Radiator with mechanical fan
- Protective grille for rotating and hot parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine coolant heater
- Steel base frame and anti-vibration isolators
- Spare external fuel tank (open set)
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel bellows supplied separately
- Static battery charger
- Manual for application and installation
- Generators Sets' voltage and frequency regulation comply with ISO 8528-5

## OPTIONAL EQUIPMENTS

### ENGINE

- Fuel-Water Seperator Filter
- Oil heater

### ALTERNATOR

- Anti-Condensation Heater
- Over sized alternator
- PMG excitation + AVR
- Main line circuit breaker

### CONTROL SYSTEM

- Automatic synchronising and power control system ( multi gen-set Parallel )
- Transition synchronization with mains
- Remote annunciator panel
- Remote relay output

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



- Alarm output relays
- Remote communication with modem
- Earth fault, single set
- Charge Ammeter

#### TRANSFER SWITCH

- Three Pole Contactor
- Four Pole Contactor
- Three or four pole motor operated circuit breaker

#### OTHER ACCESSORIES

- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Electrical oil drain pump
- Low and high fuel level alarm
- Residential silencer
- Enclosure: weater protective or sound attenuated
- Duct adapter ( on radiator)
- Inlet and outlet motorised louvers
- Inlet and outlet acoustic baffles
- Trailer
- Tool kit for maintenance
- Automatic transfer switch

### **STANDARD SPECIFICATIONS**

Compact footprint, low profile design.

Enclosure, generator set, exhaust system and fuel tank are pre-ssembled, pre-integrated and shipped as one package

Body made from steel components treated with polyester powder coating

Fire retardant foam insulation

Easy access to all service points

Exhaust system inside canopy

Large doors on each side

Control panel viewing window in a lockable access door

Emergency stop push button mounted on enclosure exterior

Cooling fan and battery charging alternator fully guarded

Fuel fill and battery can only be reached via lockable access doors.

Lifting points on the top of canopy and base frame

Customer options available to meet your applications needs.

Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of



the noise level test has been approved by the notified body Szutest

<b>CANOPY MODEL</b>		AK 100
<b>WIDTH</b>	<b>mm.</b>	2800
<b>LENGTH</b>	<b>mm.</b>	9633
<b>HEIGHT</b>	<b>mm.</b>	3307
<b>TANK CAPACITY (lt.)</b>	<b>Lt.</b>	2200

## INTRODUCTION

Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet even the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.