INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Certificate

TS ISO 8528

CE

SZUTEST

2000/14/EC

General Characteristics

Model Name	AVP 370-6
Frequency (Hz)	60
Fuel Type	Diesel
Engine Made and Model	VOLVO - TAD1341GE - 60Hz
Alternator Made and Model	Mecc Alte - ECO 38-2L/4 C - 60Hz
Control Panel Model	DSE 7320
Canopy	MS 70

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

3 Phase, 50 Hz, PF 0.8

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
480/277	370	296.00	335	268.00	445.05
380/220	365	292.00	330	264.00	554.58
208/120	370	296.00	335	268.00	1027.05

STANDBY RATING (ESP) : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

PRIME RATING (PRP) : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour perod of operation.

ENGINE SPECIFICATIONS

Engine		VOLVO
Engine Model		TAD1341GE - 60Hz
NO. OF CYLINDERS AND BUILD		6 cylinders - in line
BORE AND STROKE	**mm**	131 X 158

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

TOTAL DISPLACEMENT	**L**	12.78
Aspiration		Turbo Charged and AfterCooled
COMPRESSION RATIO		18.1:1
RATED SPEED (RPM)	**d/dk**	1800
OIL CAPACITY	**L**	36
Standby Power (kW/HP)		335/456
Prime Power		305/415
Block Heater QTY		1
Block Heater Power (Watt)		3000
Fuel Type		Diesel
Injection Type and System		Direct

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

Type of Fuel Pump		Delphi E3
Governor System		ECM
Operating Voltage (Vdc)		24 Vdc
Battery and Capacity (Qty/Ah)		2x120
Charge Alternator (A)		80
Cooling Method		Water Cooled
Cooling Fan Air Flow (m3/min)		414
Coolant Capacity (engine only / with radiator) (lt)		20/44

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

Air Filter		Dry Type	
Fuel Cons. Prime With %100 Load (lt/hr)		72.1	
Fuel Cons. Prime With %75 Load (lt/hr)		54.1	
Fuel Cons. Prime With %50 Load (lt/hr)		37.7	

ALTERNATOR SPECIFICATIONS

Manufacturer		Mecc Alte
Alternator Made and Model		ECO 38-2L/4 C - 60Hz
Frequency (Hz)	**Hz**	60
Power (kVA)	**kVA**	420
DESIGN		4 Pole, Brushless
VOLTAGE	**V**	480

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

Phase		3
A.V.R.		DSR
Voltage Regulation	**(+/-)**	1
Insulation System		H
Protection		IP23
Rated Power Factor		0.8
WEIGHT COMP. GENERATOR (Kg)		895
COOLING AIR (m^3/min)	**m^3**	32

SIZE and WEIGHT

Open Type	**DRY WEIGHT (kg.) (kg.)**	**LENGTH (mm.)**	**WIDTH (mm.)**	**HEIGHT (mm.)**	**TANK CAPACITY (lt.) (Lt.)**
Image not found or type unknown		3050	1550	1860	700
CANOPY	**DRY WEIGHT (kg.) (kg.)**	**LENGTH (mm.)**	**WIDTH (mm.)**	**HEIGHT (mm.)**	**TANK CAPACITY (lt.) (Lt.)**

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

MS 70 Image not found or type unknown	3930	4434	1606	2496	700

STANDART SPECIFICATIONS

Water cooled, Diesel engine
Radiator with mechanical fan
Protective grille for rotating and hot parts
Electric starter and charge alternator
Starting battery (with lead acid) including rack and cables
Engine coolant heater
Base frame design incorporates an integral fuel tank and anti-vibration isolators
Flexible fuel connection hoses
Single bearing, class H alternator
Industrial exhaust silencer and steel bellows supplied separately(for open sets)
Static battery charger
Manual for application and installation

OPTIONAL EQUIPMENTS

ENGINE
• Fuel-Water Seperator Filter
• Oil heater
ALTERNATOR
• Anti-Condensation Heater
• Over sized alternator
• Main line circuit breaker
CONTROL SYSTEM
• Remote annunciator panel
• Remote relay output
• Alarm output relays
• Remote communication with modem
• Earth fault, single set
• Charge Ammeter
TRANSFER SWITCH
• Three or four pole contactor

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

- Three or four pole motor operated circuit breaker

OTHER ACCESSORIES

- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Electrical oil drain pump
- Residential silencer
- Enclosure: weater protective or sound attenuated
- Duct adapter (on radiator)
- Inlet and outlet motorised louvers
- Inlet and outlet acoustic baffles
- Trailer
- Tool kit for maintenance
- Supplied with oil and coolant - 30 °C
- Battery isolating switch

INTRODUCTION

Sound-attenuated and weather-protective enclosures for generating sets from Aksa, meet event the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

STANDARD SPECIFICATIONS

Compact footprint, low profile design.
Enclosure, generator set, exhaust system and fuel tank are pre-assembled, pre-integrated and shipped as one package
Body made from steel components treated with polyester powder coating
Fire retardant foam insulation
Easy access to all service points
Exhaust system inside canopy
Large doors on each side
Control panel viewing window in a lockable access door
Emergency stop push button mounted on enclosure exterior
Cooling fan and battery charging alternator fully guarded
Fuel fill and battery can only be reached via lockable access doors.
Lifting points on the top of canopy and base frame
Customer options available to meet your application's needs.
Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.

the noise level test has been approved by the notified body Szutest

CANOPY MODEL		MS 70
WIDTH	**mm.**	1606
LENGTH	**mm.**	4434
HEIGHT	**mm.**	2424
TANK CAPACITY (lt.)	**Lt.**	700

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.