



INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Certificate

ISO 14001-2004

TS ISO 8528

TS ISO 9001-2008

CE

SZUTEST

2000/14/EC

General Characteristics

Model Name	AP 1900-6
Frequency (Hz)	60
Fuel Type	Diesel
Engine Made and Model	PERKINS - 4012-46TAG3A - 60Hz
Alternator Made and Model	Mecc Alte - ECO 46-2S/4 A (380V) - 60Hz
Control Panel Model	DSE 7320

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.


Canopy

AK 99-AP1875

3 Phase, 50 Hz, PF 0.8

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
480/277	1900	1520.00	1740	1392.00	2285.41
380/220	1890	1512.00	1720	1376.00	2871.64

STANDBY RATING (ESP) : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

PRIME RATING (PRP) : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

ENGINE SPECIFICATIONS

Engine	PERKINS
Engine Model	4012-46TAG3A - 60Hz
NO. OF CYLINDERS AND BUILD	12 cylinders - V type
BORE AND STROKE	mm 160 X 190

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



TOTAL DISPLACEMENT	L	45.842	
Aspiration		Turbo Charged	
COMPRESSION RATIO		13.0:1	
RATED SPEED (RPM)	d/dk	1800	
OIL CAPACITY	L	177	
Standby Power (kW/HP)		1643/2203	
Prime Power		1500/2011	
Block Heater QTY			
		2	
Block Heater Power (Watt)			
		3000	
Fuel Type			
		Diesel	
Injection Type and System			
		Direct	



Type of Fuel Pump			
		Mechanical	
Governor System			
		Electronic	
Operating Voltage (Vdc)			
		24 Vdc	
Battery and Capacity (Qty/Ah)			
		4x143	
Charge Alternator (A)			
		40	
Cooling Method			
		Water Cooled	
Cooling Fan Air Flow (m3/min)			
		2160	
Coolant Capacity (engine only / with radiator) (lt)			
		225	



Air Filter			
		Dry Type	
Fuel Cons. Prime With %100 Load (lt/hr)			
		356	
Fuel Cons. Prime With %75 Load (lt/hr)			
		277	
Fuel Cons. Prime With %50 Load (lt/hr)			
		185	

ALTERNATOR SPECIFICATIONS


Manufacturer		Mecc Alte
Alternator Made and Model		ECO 46-2S/4 A (380V) - 60Hz
Frequency (Hz)	Hz	60
Power (kVA)	kVA	1480
DESIGN		Brushless
VOLTAGE	V	380

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Phase		3
A.V.R.		DER1
Voltage Regulation	(+/-)	0.5
Insulation System		H
Protection		IP23
Rated Power Factor		0.8
WEIGHT COMP. GENERATOR (Kg)		3565
COOLING AIR (m³/min)	m³	162

SIZE and WEIGHT

Open Type	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
		5816	2220	2787	2000
CANOPY	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



AK 99-AP1875 Image not found of type unknown		900	2800	3456	2200
---	--	-----	------	------	------

STANDART SPECIFICATIONS

- Water cooled diesel engine
- Radiator with mechanical fan
- Protective grille for rotating and hot parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine coolant heater
- Steel base frame and anti-vibration isolators
- Spare external fuel tank (open set)
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel bellows supplied separately
- Static battery charger
- Manual for application and installation

OPTIONAL EQUIPMENTS

ENGINE

- Remote Radiator Cooling
- Fuel-Water Seperator Filter
- Oil heater

ALTERNATOR

- Anti-Condensation Heater
- Over sized alternator
- Main line circuit breaker

CONTROL SYSTEM

- Automatic synchronising and power control system (multi gen-set Parallel)
- Transition synchronization with mains
- Remote annunciator panel
- Remote relay output
- Alarm output relays
- Remote communication with modem

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



- Earth fault, single set
 - Charge Ammeter
- TRANSFER SWITCH
- Three or four pole contactor
 - Three or four pole motor operated circuit breaker
- OTHER ACCESSORIES
- Main Fuel Tank
 - Automatic or manual fuel filling system
 - Manual oil drain pump
 - Electrical oil drain pump
 - Low and high fuel level alarm
 - Residential silencer
 - Enclosure: weater protective or sound attenuated
 - Duct adapter (on radiator)
 - Inlet and outlet motorised louvers
 - Inlet and outlet acoustic baffles
 - Tool kit for maintenance
 - 1500/3000 hours maintenance kit
 - Supplied with oil and coolant - 30 °C