



## INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

### Certificate

TS ISO 8528

CE

SZUTEST

2000/14/EC

### General Characteristics

<b>Model Name</b>	AC 2500
<b>Frequency (Hz)</b>	50
<b>Fuel Type</b>	Diesel
<b>Engine Made and Model</b>	CUMMINS - QSK60-G8
<b>Alternator Made and Model</b>	Mecc Alte - ECO 46-1.5L/4 A
<b>Control Panel Model</b>	DSE 7320
<b>Canopy</b>	AK 99


**3 Phase, 50 Hz, PF 0.8**

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
400/231	2500	2000.0	-	-	3608.55

**STANDBY RATING (ESP)** : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

**PRIME RATING (PRP)** : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

### ENGINE SPECIFICATIONS

<b>Engine</b>		CUMMINS
<b>Engine Model</b>		QSK60-G8
<b>NO. OF CYLINDERS AND BUILD</b>		16 cylinders - V type
<b>BORE AND STROKE</b>	<b>mm</b>	159 X 190
<b>TOTAL DISPLACEMENT</b>	<b>L</b>	60.2
<b>Aspiration</b>		Turbocharged and Low Temperature Aftercooled

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>COMPRESSION RATIO</b>		14.5:1	
<b>RATED SPEED (RPM)</b>	<b>d/dk</b>	1500	
<b>OIL CAPACITY</b>	<b>L</b>	176	
<b>Standby Power (kW/HP)</b>		2145/2876.5	
<b>Block Heater QTY</b>			
		2	
<b>Block Heater Power (Watt)</b>			
		3000	
<b>Fuel Type</b>			
		Diesel	
<b>Injection Type and System</b>			
		Direct	
<b>Type of Fuel Pump</b>			
		Cummins HPI-PT	
<b>Governor System</b>			
		Electronic	

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



<b>Operating Voltage (Vdc)</b>			
		24 Vdc	
<b>Battery and Capacity (Qty/Ah)</b>			
		4x143	
<b>Charge Alternator (A)</b>			
		55	
<b>Cooling Method</b>			
		Water Cooled	
<b>Cooling Fan Air Flow (m3/min)</b>			
		2570	
<b>Coolant Capacity (engine only / with radiator) (lt)</b>			
		159/	
<b>Air Filter</b>			
		Dry Type	
<b>Fuel Cons. Prime With %100 Load (lt/hr)</b>			
		449	



<b>Fuel Cons. Prime With %75 Load (lt/hr)</b>			
			335
<b>Fuel Cons. Prime With %50 Load (lt/hr)</b>			
			228



### ALTERNATOR SPECIFICATIONS

<b>Manufacturer</b>		Mecc Alte
<b>Alternator Made and Model</b>		ECO 46-1.5L/4 A
<b>Frequency (Hz)</b>	<b>Hz</b>	50
<b>Power (kVA)</b>	<b>kVA</b>	2300
<b>DESIGN</b>		4 Pole, Brushless
<b>VOLTAGE</b>	<b>V</b>	400
<b>Phase</b>		3
<b>A.V.R.</b>		DER1
<b>Voltage Regulation</b>	<b>(+/-)</b>	0.5



<b>Insulation System</b>	H
<b>Protection</b>	IP23
<b>Rated Power Factor</b>	0.8
<b>WEIGHT COMP. GENERATOR (Kg)</b>	4260
<b>COOLING AIR (m<sup>3</sup>/min)</b>	m <sup>3</sup> 135

### SIZE and WEIGHT

Open Type	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
		5716	2408	3130	2000
CANOPY	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
AK 99 	22000	9000	2800	3456	2200

### STANDART SPECIFICATIONS

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Water cooled diesel engine  
Radiator with mechanical fan  
Protective grille for rotating and hot parts  
Electric starter and charge alternator  
Starting battery (with lead acid) including rack and cables  
Engine coolant heater  
Steel base frame and anti-vibration isolators  
Spare external fuel tank (open set)  
Flexible fuel connection hoses  
Single bearing, class H alternator  
Industrial exhaust silencer and steel bellows supplied separately  
Static battery charger  
Manual for application and installation  
Generators Sets' voltage and frequency regulation comply with ISO 8528-5

### **OPTIONAL EQUIPMENTS**

#### **ENGINE**

- Remote Radiator Cooling
- Electronic governor control
- Fuel-Water Separator Filter
- Low water level alarm
- Oil heater

#### **ALTERNATOR**

- Anti-Condensation Heater
- Over sized alternator
- PMG excitation + AVR
- Single Phase ( 4 lead)
- Main line circuit breaker

#### **CONTROL SYSTEM**

- Automatic synchronising and power control system ( multi gen-set Parallel )
- Parallel system with mains.
- Transition synchronization with mains
- Remote annunciator panel
- Remote relay output
- Alarm output relays
- Remote communication with modem
- Earth fault, single set
- Charge Ammeter

**TRANSFER SWITCH**

- Three Pole Contactor
- Four Pole Contactor
- Three or four pole contactor
- Motorlu Şalter
- Three or four pole motor operated circuit breaker

**OTHER ACCESSORIES**

- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Electrical oil drain pump
- Low and high fuel level alarm
- Residential silencer
- Enclosure: weater protective or sound attenuated
- Duct adapter ( on radiator)
- Inlet and outlet motorised louvers
- Inlet and outlet acoustic baffles
- Trailer
- Tool kit for maintenance
- 1500/3000 hours maintenance kit
- Double wall chassis
- Supplied with oil and coolant - 30 °C
- Battery isolating switch
- Battery heater
- Automatic transfer switch

**STANDARD SPECIFICATIONS**

Compact footprint, low profile design.

Enclosure, generator set, exhaust system and fuel tank are pre-assembled, pre-integrated and shipped as one package

Body made from steel components treated with polyester powder coating

Fire retardant foam insulation

Easy access to all service points

Exhaust system inside canopy

Large doors on each side

Control panel viewing window in a lockable access door

Emergency stop push button mounted on enclosure exterior

Cooling fan and battery charging alternator fully guarded

Fuel fill and battery can only be reached via lockable access doors.

Lifting points on the top of canopy and base frame





Customer options available to meet your application's needs.

Aksa makes its generating sets' noise level tests in accordance with directive 2000/14/EC validation of the noise level test has been approved by the notified body Szutest

<b>CANOPY MODEL</b>		AK 99
<b>WIDTH</b>	<b>mm.</b>	2800
<b>LENGTH</b>	<b>mm.</b>	9000
<b>HEIGHT</b>	<b>mm.</b>	3456
<b>TANK CAPACITY (lt.)</b>	<b>Lt.</b>	2200

## INTRODUCTION

Sound-attenuated and weather-protective enclosures for generating sets from Aksa, meet even the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.